

### 8.3 HVAC CBL 18AWG,STR,1TP,CMR

### H-TP18-CMR

#### WIRE AND CABLE SPECIFICATION - Required Information:

Description HVAC CBL 18AWG,STR,1TP,CMR
---

#### Specifications:

Number of pairs	: 1	Resistance	: $\Omega$ /ft nom.
Gauge and stranding	: 18AWG (STRAND)	Capacitance	: NA
Primary insulation type	: PVC	Twists per foot	: 4 nominal
Nom Insulation thickness	: 0.010"	Jacket Material	: PVC
Color code	: BLK/WHT	Nom Jacket thicknes	: 0.020"
Shield type (Tape, Braid)	: NA	Jacket color	: BLUE
Shield coverage	: NA	Nominal O.D.	: 0.172"
Tape	: NA	Packaging	: 1000 ft
Drain wire	: NA	UL type	: CMR
Braid construction	: NA	Voltage rating	: 300V
Impedance (1, 10, 100Mhz)	: NA	Temp rating	: 75°C MIN

Print Legend: NORTHFLEX® H-TP18-CMR "DI, DO, AI, AO" (Mfg E#) 18AWG 1P 75°C CMR (UL) C(UL)

Note: Sequential footage markers (1000 descending to 0) required