



E³Point SPECIFICATIONS

Toxic and Combustible Gas Detector Standalone Platform (Single or Dual-Gas Monitoring)



General Specifications					
Uses	Wall or duct-mounted gas detector for monitoring carbon monoxide (CO), nitrogen dioxide (NO ₂), oxygen (O ₂), methane (CH ₄), hydrogen (H ₂), hydrogen sulphide (H ₂ S), and propane (C ₃ H ₈), installed as a standalone device with single-gas or dual-gas monitoring. (Note: E³Point standalone version replaces Vulcain models VA201T, VA201M and VA301M)				
Size	20.56 x 14.90 x 6.72cm (8.09 x 5.87 x 2.65") (H x W x D); Remote Sensor: 3.5 x 4.5 x 6.5 cm (1.36 x 1.75 x 2.56")				
Power Requirement	24 Vac nominal (17-27Vac), 50/60 Hz, 0.35 A; 24Vdc nominal (20-38Vdc); with remote sensor: 7 W max.				
Optional Main AC Input	120Vac nominal, +/- 10% (with on-board transformer)				
Relay Output	2 DPDT relays, 5A @ 250Vac; 5A @ 30Vdc				
Communications	4-20mA				
Operating Environment	Commercial, Indoor, Extreme Temperature Environments				
Operating Temperature	H ₂ S, NO ₂ , O ₂ , CH ₄ , H ₂ , C ₃ H ₈ : -40 to 50°C (-40 to 122°F) CO: -20 to 50°C (-4 to 122°F); future available CO version: -40 to 50°C (-40 to 122°F)				
Sensor Type	Electrochemical cell (CO, NO ₂ , H ₂ S, O ₂); catalytic (CH ₄ , H ₂ , C ₃ H ₈)				
Display	8 character, 2 line backlit LCD				
Visual Indicators	Green LED: Power Amber LED 1: Alarm/Fault Amber LED 2: Alarm/Fault				
Audible Alarm	>85 dBA at 3 m (10 ft)				
Accuracy	+/- 3% of full scale @ 25 C				
Detection Ranges and Alarm Levels					
Gas	Resolution	Range	Alarm A	Alarm B	Alarm C
CO (Carbon monoxide)	1 ppm	0-250 ppm	25 ppm	200 ppm	225 ppm
H₂S (Hydrogen sulfide)	0.1 ppm	0-50 ppm	10 ppm	15 ppm	20 ppm
NO₂ (Nitrogen dioxide)	0.1 ppm	0-10 ppm	0.7 ppm	2 ppm	9 ppm
O₂ (Oxygen)	0.1% vol.	0-25% vol.	19.5% vol.	22% vol.	22.5% vol.
H₂ (Hydrogen)	0.5% LEL	0-100% LEL	25% LEL	50% LEL	90% LEL
CH₄ (Methane)	0.5% LEL	0-100% LEL	25% LEL	50% LEL	90% LEL
C₃H₈ (Propane)	0.5% LEL	0-100% LEL	25% LEL	50% LEL	90% LEL
Enclosure					
	Polycarbonate				
Certification					
	 CSA C22.2 No. 61010-1,  UL 61010-1; FCC part 15; ICES-003 issue 4				

ORDERING INFORMATION

Single-Gas Configuration: Base Unit, Surface-Mount

** Base unit and sensor cartridge sold together ** Base unit only; sensor cartridge sold separately*

Part Number	Description
E3SASCO*	E ³ Point, CO sensor cartridge, Surface-mount, 24Vac/dc, -20 to 50°C (-4 to 122°F)
E3SA**	E ³ Point, Surface-mount, 4-20mA, 24Vac/dc, -40 to 50°C (-40 to 122°F)
E3SAHSCO*	E ³ Point, CO sensor cartridge, Surface-mount, 120Vac, -20 to 50°C (-4 to 122°F)
E3SAH**	E ³ Point, Surface-mount, 4-20mA, 120Vac, -40 to 50°C (-40 to 122°F)

Dual-Gas Configuration: Base Unit w/Remote Sensor Capability, Surface-Mount

Part Number	Description
E3SARSCO*	E ³ Point, CO sensor cartridge, Surface-mount, 24Vac/dc, Dual-mode, -20 to 50°C (-4 to 122°F)
E3SAR**	E ³ Point, Surface-mount, 4-20mA, 24Vac/dc, Dual-mode, -40 to 50°C (-40 to 122°F)
E3SARHSCO*	E ³ Point, CO sensor cartridge, Surface-mount, 120Vac, Dual-mode, -20 to 50°C (-4 to 122°F)
E3SARH**	E ³ Point, Surface-mount, 4-20mA, 120Vac, Dual-mode, -40 to 50°C (-40 to 122°F)

Remote Sensors (always sold with sensor cartridge included)

Part Number	Description
E3SRMCO	E ³ Point, Remote Sensor, -20 to 50°C (-4 to 122°F), Carbon Monoxide
E3SRMNO2	E ³ Point, Remote Sensor, -20 to 50°C (-4 to 122°F), Nitrogen Dioxide
E3SRMH2S	E ³ Point, Remote Sensor, -20 to 50°C (-4 to 122°F), Hydrogen Sulfide
E3SRMH2	E ³ Point, Remote Sensor, -20 to 50°C (-4 to 122°F), Hydrogen
E3SRMO2	E ³ Point, Remote Sensor, -20 to 50°C (-4 to 122°F), Oxygen
E3SRMM	E ³ Point, Remote Sensor, -20 to 50°C (-4 to 122°F), Methane
E3SRMP	E ³ Point, Remote Sensor, -20 to 50°C (-4 to 122°F), Propane

Stand-Alone Platform, Duct-Mount

Part Number	Description
E3DASCO*	E ³ Point, CO, Duct-mount, 24Vac/dc, -20 to 50°C (-4 to 122°F)
E3DA**	E ³ Point, Duct-mount, 4-20mA, 24Vac/dc, -40 to 50°C (-40 to 122°F)

Sensor Cartridges

Part Number	Description
E3SCO	CO Cartridge -20 to 50°C (-4 to 122°F), Carbon Monoxide
E3NO2	NO ₂ Cartridge -40 to 50°C (-40 to 122°F), Nitrogen Dioxide
E3H2S	H ₂ S Cartridge -40 to 50°C (-40 to 122°F), Hydrogen Sulfide
E3H2	H ₂ Cartridge -40 to 50°C (-40 to 122°F), Hydrogen
E3O2	O ₂ Cartridge -40 to 50°C (-40 to 122°F), Oxygen
E3M	CH ₄ Cartridge -40 to 50°C (-40 to 122°F), Methane
E3P	C ₃ H ₈ Cartridge -40 to 50°C (-40 to 122°F), Propane

EXAMPLES OF HOW TO ORDER

To order a stand-alone version, surface-mount, analog, CO detector, -20 to 50°C (-4 to 122°F): Order E3SASCO

To order a stand-alone version, surface-mount, analog, dual-gas CO + NO₂, -20 to 50°C (-4 to 122°F): Order E3SARSCO + E3SRMNO2

To order a stand-alone version, duct-mount, analog, propane detector, -40 to 50°C (-40 to 122°F): Order E3DA + E3P

To order a stand-alone version, surface-mount, analog, dual-gas CO + C₃H₈, 120Vac, -20 to 50°C (-4 to 122°F): Order E3SARHSCO + E3SRMP

Find out more

www.honeywellanalytics.com

Toll free: 1 800 563 2967

Please Note:

While every effort has been made to ensure accuracy in this publication, no responsibility can be accepted for errors or omissions. Data may change, as well as legislation, and you are strongly advised to obtain copies of the most recently issued regulations, standards, and guidelines. This publication is not intended to form the basis of a contract.

Honeywell